

Serial No. 10/673,027  
60130-1894;02MRA0144

**AMENDMENT**

**IN THE CLAIMS:**

1. (CURRENTLY AMENDED) A system that detects an obstruction in a path of an openable vehicle member, comprising:
  - a direct detector that directly detects the obstruction; and
  - an indirect detector that indirectly detects the obstruction and outputs openable member position information to the direct detector, wherein only the direct detector is provided with the openable member position information.
2. (PREVIOUSLY PRESENTED) The system of claim 1, wherein the indirect detector detects a force exerted by the obstruction on the openable vehicle member.
3. (PREVIOUSLY PRESENTED) The system of claim 1, wherein the direct detector comprises:
  - a light sensor that receives light in a vicinity of the obstruction; and
  - an analysis circuit that conducts an analysis of the light received by the light sensor.
4. (PREVIOUSLY PRESENTED) The system of claim 3, wherein the analysis circuit conducts the analysis by comparing a distribution of the light received by the light sensor to a reference distribution.
5. (ORIGINAL) The system of claim 3, wherein the light sensor is a charge coupled device sensor.
6. (PREVIOUSLY PRESENTED) The system of claim 1, wherein the direct detector detects the obstruction according to the openable member position information provided by the indirect detector.

Serial No. 10/673,027  
60130-1894;02MRA0144

7. (CURRENTLY AMENDED) A method for detecting an obstruction in a path of an openable member, comprising the steps of:
  - indirectly detecting the obstruction by detecting a force exerted by the obstruction on the openable member using an indirect detector;
  - outputting openable member position information; ~~and~~
  - directly detecting the obstruction in the path of the openable member with a direct detector based on the openable member position information; and
  - providing the openable member position information to only the direct detector.
8. (ORIGINAL) The method of claim 7, wherein the step of directly detecting the obstruction comprises detecting a light distribution along a closing line of the openable member.
9. (CURRENTLY AMENDED) The method of claim 8, wherein the step of directly detecting the obstruction comprises:
  - comparing the light distribution along the closing line with a reference distribution; and
  - indicating a presence of the obstruction when the ~~comparisen~~ comparing step shows a variation between the light distribution and the reference distribution.
10. (PREVIOUSLY PRESENTED) The method of claim 9, wherein the step of directly detecting the obstruction further comprises the step of updating the reference distribution based on the openable member position information.
11. (ORIGINAL) The method of claim 9, wherein the reference distribution is based on the openable member position information.
12. (PREVIOUSLY PRESENTED) The method of claim 9, wherein the indicating step indicates the presence of the obstruction when the comparing step shows that the variation between the light distribution and the reference distribution is greater than a predetermined threshold.

Serial No. 10/673,027  
60130-1894;02MRA0144

13. (ORIGINAL) The method of claim 12, wherein the predetermined threshold is variable based on the openable member position information.
14. (CURRENTLY AMENDED) An anti-trapping system for an openable vehicle member, comprising:
  - a drive system that controls movement of the openable vehicle member;
  - an indirect detector that detects a force exerted by an obstruction on the openable vehicle member; and
  - a direct detector comprising:
    - a light sensor that detects a light distribution affected by the obstruction and receives openable member position information from the indirect detector, wherein only the direct detector is provided with the openable member position information, and
    - an analysis circuit that conducts an analysis of light received by the light sensor and outputs an interruption signal to the drive system to stop movement of the openable vehicle member if the obstruction is detected.
15. (PREVIOUSLY PRESENTED) The system of claim 14, wherein the analysis circuit compares the light distribution received by the light sensor to a reference distribution.
16. (ORIGINAL) The system of claim 14, wherein the light sensor is a charge coupled device sensor.
17. (ORIGINAL) The system of claim 14, wherein the direct detector detects the obstruction according to the openable member position information provided by the indirect detector.